

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.12.2011

Version number 8

Revision: 07.12.2011

1 Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name: Release Agent Mikon® MG-9006

Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the preparation Release Agent

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Muench Chemie International GmbH

Viernheimer Strasse 70 - 76

D-69469 Weinheim

GERMANY

Phone: +49 (6201) 99 83 - 0

Fax: +49 (6201) 1 71 95

Mail: info@muench-chemie.com

Web: www.muench-chemie.com


Further information obtainable from: Laboratory

Emergency telephone number: Muench Chemie International GmbH: +49 (6201) 99 83 - 0 or +49 (171) 37 37 502


2 Hazards identification

Classification of the substance or mixture


Classification according to Directive 67/548/EEC or Directive 1999/45/EC

 Xn; Harmful


R65: Harmful: may cause lung damage if swallowed.

 Xi; Irritant

R38: Irritating to skin.

 F; Highly flammable

R11: Highly flammable.

 N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Has a narcotizing effect.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

Label elements

Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:

Xn Harmful

F Highly flammable

N Dangerous for the environment

Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light, < 0,1 % Benzene

Naphtha (petroleum), hydrotreated heavy

Risk phrases:

11 Highly flammable.

38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

67 Vapours may cause drowsiness and dizziness.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.12.2011

Version number 8

Revision: 07.12.2011

Trade name: Release Agent Mikon® MG-9006

(Contd. of page 1)

Safety phrases:

- 9 Keep container in a well-ventilated place.
 16 Keep away from sources of ignition - No smoking.
 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
 33 Take precautionary measures against static discharges.
 51 Use only in well-ventilated areas.
 57 Use appropriate container to avoid environmental contamination.

Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture: consisting of the following components.

Dangerous components:

CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light, < 0,1 % Benzene	> 50%
EINECS: 265-151-9	Xn R65; Xi R38; F R11; N R51/53	
	R67	
	Carc. Cat. 3, Muta. Cat. 3	
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	10 - 20%
EINECS: 265-150-3	Xn R65	
	R10-66-67	
	Carc. Cat. 3, Muta. Cat. 3	

Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

Description of first aid measures**General information:**

Take affected persons out of danger area and lay down.

Immediately remove any clothing soiled by the product.

After inhalation: In case of unconsciousness place patient stably in side position for transportation.**After skin contact:**

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water.**After swallowing:** If symptoms persist consult doctor.**Information for doctor:****Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

Nausea

Unconsciousness

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

Extinguishing media**Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.**For safety reasons unsuitable extinguishing agents:**

Water

Water with full jet

Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Advice for firefighters**Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.12.2011

Version number 8

Revision: 07.12.2011

Trade name: Release Agent Mikon® MG-9006

(Contd. of page 2)

Additional information

Cool endangered receptacles with water spray.
 Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation
 Keep away from ignition sources.
 Avoid contact with the eyes and skin.
 Immediately remove all soiled and contaminated clothing
 Do not inhale gases / fumes / aerosols.
 Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow to penetrate the ground/soil.
 Prevent seepage into sewage system, workpits and cellars.
 Inform respective authorities in case of seepage into water course or sewage system.
 Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to item 13.
 Ensure adequate ventilation.
 Do not flush with water or aqueous cleansing agents
 Dispose of the material collected according to regulations.

Reference to other sections

See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage**Handling:****Precautions for safe handling**

Store in cool, dry place in tightly closed receptacles.
 Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
 Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.

Information about fire - and explosion protection:

Fumes can combine with air to form an explosive mixture.
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Provide solvent resistant, sealed floor.
 Store in a cool location.

Information about storage in one common storage facility: Store away from oxidizing agents.

Further information about storage conditions:

Store receptacle in a well ventilated area.
 Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
 Keep container tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

Control parameters**Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.12.2011

Version number 8

Revision: 07.12.2011

Trade name: Release Agent Mikon® MG-9006

(Contd. of page 3)

Additional information: The lists valid during the making were used as basis.

Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

Do not eat, drink, smoke or sniff while working.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.

Respiratory protection:

Short term filter device:

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed goggles

Body protection: Protective work clothing

9 Physical and chemical properties

Information on basic physical and chemical properties**General Information****Appearance:**

Form: Fluid
Colour: White
Odour: Characteristic
Odour threshold: Not determined.

pH-value: Not determined.

Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 180 °C

Flash point: < 0 °C

Flammability (solid, gaseous): Not applicable.

Ignition temperature: 240 °C

Decomposition temperature: Not determined.

Self-igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower: 0,6 Vol %

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.12.2011

Version number 8

Revision: 07.12.2011

Trade name: Release Agent Mikon® MG-9006

(Contd. of page 4)

Upper:	7,0 Vol %
Vapour pressure at 20°C:	1 hPa
Density at 20°C:	0,74 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Segregation coefficient (n-octanol/water):	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	73,0 %
Other information	No further relevant information available.

10 Stability and reactivity

Reactivity

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:

64742-49-0 Naphtha (petroleum), hydrotreated light, < 0,1 % Benzene

Oral LD50 > 2000 mg/kg (Ratte)

Dermal LD50 > 2000 mg/kg (rbt)

Inhalative LC50/4 h > 5 mg/l (Ratte)

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral LD50 >5000 mg/kg (Ratte)

Dermal LD50 >3000 mg/kg (rab)

Primary irritant effect:

on the skin: Irritant to skin and mucous membranes.

on the eye: No irritating effect.

Sensitization: No sensitizing effects known.

Additional toxicological information:

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

Toxicity

Acquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Behaviour in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Toxic for fish

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.12.2011

Version number 8

Revision: 07.12.2011

Trade name: Release Agent Mikon® MG-9006

(Contd. of page 5)

Additional ecological information:**General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**Other adverse effects** No further relevant information available.**13 Disposal considerations****Waste treatment methods****Recommendation**

Must be specially treated adhering to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.**14 Transport information****UN-Number****ADR, IMDG, IATA**

UN1993

UN proper shipping name**ADR**

1993 FLAMMABLE LIQUID, N.O.S. (vapor pressure at 50 °C at most 110 kPa) (Naphtha (petroleum), hydrotreated light, < 0,1 % Benzene)

IMDG, IATA

FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), hydrotreated light, < 0,1 % Benzene)

Transport hazard class(es)**ADR****Class**

3 Flammable liquids.

Label

3

IMDG, IATA**Class**

3 Flammable liquids.

Label

3

Packing group**ADR, IMDG, IATA**

II

Environmental hazards:**Marine pollutant:**

No

Special marking (ADR):

Symbol (fish and tree)

Special precautions for user

Warning: Flammable liquids.

Danger code (Kemler):

33

EMS Number:F-E,S-E**Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

Transport/Additional information:**ADR****Tunnel restriction code**

D/E

 EU
 (Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.12.2011

Version number 8

Revision: 07.12.2011

Trade name: Release Agent Mikon® MG-9006

(Contd. of page 6)

15 Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations:****Technical instructions (air):****Class Share in %****NK > 50****Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

R10 Flammable.

R11 Highly flammable.

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Department issuing MSDS: Laboratory**Contact:** Mr. Marek*** Data compared to the previous version altered.**

EU