

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.12.2011

Version number 5

Revision: 08.12.2011

1 Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name: Sealer MK-749

Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the preparation Release Agent

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Muench Chemie International GmbH

Viernheimer Strasse 70 - 76

D-69469 Weinheim

GERMANY

Phone: +49 (6201) 99 83 - 0

Fax: +49 (6201) 1 71 95

Mail: info@muench-chemie.com

Web: www.muench-chemie.com


Further information obtainable from: Laboratory

Emergency telephone number: Muench Chemie International GmbH: +49 (6201) 99 83 - 0 or +49 (171) 37 37 502


2 Hazards identification

Classification of the substance or mixture


Classification according to Directive 67/548/EEC or Directive 1999/45/EC

 Xn; Harmful

R20/21-65: Harmful by inhalation and in contact with skin. Harmful: may cause lung damage if swallowed.

 Xi; Irritant

R37/38: Irritating to respiratory system and skin.

 N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R10: Flammable.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

Label elements

Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:

Xn Harmful

N Dangerous for the environment

Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom., < 0,1 % Benzene
xylene

Risk phrases:

10 Flammable.

20/21 Harmful by inhalation and in contact with skin.

37/38 Irritating to respiratory system and skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

Safety phrases:

23 Do not breathe fumes/aerosol.

24/25 Avoid contact with skin and eyes.

57 Use appropriate container to avoid environmental contamination.

62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2011

Version number 5

Revision: 08.12.2011

Trade name: Sealer MK-749

(Contd. of page 1)

Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**3 Composition/information on ingredients****Chemical characterization: Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 1330-20-7	xylene	> 50%
EINECS: 215-535-7	Xn R20/21; Xi R38 R10	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom., < 0,1 % Benzene	20 - 50%
EINECS: 265-199-0	Xn R65; N R51/53 R10-66-67 Carc. Cat. 3, Muta. Cat. 3	

Additional information: For the wording of the listed risk phrases refer to section 16.**4 First aid measures****Description of first aid measures****General information:**

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.**After swallowing:** Do not induce vomiting; call for medical help immediately.**Information for doctor:****Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

Nausea

Hazards Danger of pulmonary oedema.**Indication of any immediate medical attention and special treatment needed** No further relevant information available.**5 Firefighting measures****Extinguishing media****Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**For safety reasons unsuitable extinguishing agents:** Water with full jet**Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide (CO)

Advice for firefighters**Protective equipment:**

Wear fully protective suit.

Wear self-contained respiratory protective device.

6 Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Wear protective clothing.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2011

Version number 5

Revision: 08.12.2011

Trade name: Sealer MK-749

(Contd. of page 2)

Keep away from ignition sources.

Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Dispose contaminated material as waste according to item 13.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:**Precautions for safe handling**

Store in cool, dry place in tightly closed receptacles.

Ensure that suitable extractors are available on processing machines

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Fumes can combine with air to form an explosive mixture.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:** Provide solvent resistant, sealed floor.**Information about storage in one common storage facility:**

Do not store together with oxidizing and self-inflammable substances

The official regulations have to be considered.

Further information about storage conditions:

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Keep container tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.**Control parameters****Ingredients with limit values that require monitoring at the workplace:****1330-20-7 xylene**IOELV Short-term value: 442 mg/m³, 100 ppmLong-term value: 221 mg/m³, 50 ppm

Skin

Additional information: The lists valid during the making were used as basis.**Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

Do not eat, drink, smoke or sniff while working.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2011

Version number 5

Revision: 08.12.2011

Trade name: Sealer MK-749

(Contd. of page 3)

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed goggles

Body protection: Protective work clothing

9 Physical and chemical properties

Information on basic physical and chemical properties**General Information****Appearance:**

Form:	Fluid
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	140 °C

Flash point: 30 °C**Ignition temperature:** 450 °C**Decomposition temperature:** Not determined.**Self-igniting:** Product is not selfigniting.**Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.**Explosion limits:**

Lower:	0,7 Vol %
Upper:	7,5 Vol %

Vapour pressure at 20 °C: 6,7 hPa**Density at 20 °C:** 0,86 g/cm³**Relative density** Not determined.**Vapour density** Not determined.**Evaporation rate** Not determined.**Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

Segregation coefficient (n-octanol/water): Not determined.**Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

Solvent content:

Organic solvents:	97,7 %
Solids content:	2,0 %

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.12.2011

Version number 5

Revision: 08.12.2011

Trade name: Sealer MK-749

Other information

No further relevant information available.

(Contd. of page 4)

* **10 Stability and reactivity**

Reactivity**Chemical stability****Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.**Possibility of hazardous reactions** No dangerous reactions known.**Conditions to avoid** No further relevant information available.**Incompatible materials:** No further relevant information available.**Hazardous decomposition products:** No dangerous decomposition products known.

* **11 Toxicological information**

Information on toxicological effects**Acute toxicity:****LD/LC50 values relevant for classification:****1330-20-7 xylene**

Oral LD50 4300 mg/kg (Ratte)

Dermal LD50 2000 mg/kg (rbt)

64742-95-6 Solvent naphtha (petroleum), light arom., < 0,1 % Benzene

Oral LD50 >6800 mg/kg (Ratte)

Dermal LD50 >3400 mg/kg (rab)

Inhalative LC50/4 h >10,2 mg/l (Ratte)

Primary irritant effect:**on the skin:** Irritant to skin and mucous membranes.**on the eye:** No irritating effect.**Sensitization:** No sensitizing effects known.**Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

* **12 Ecological information**

Toxicity**Aquatic toxicity:** No further relevant information available.**Persistence and degradability** No further relevant information available.**Other information:** The product is biodegradable.**Behaviour in environmental systems:****Bioaccumulative potential** No further relevant information available.**Mobility in soil** No further relevant information available.**Ecotoxicological effects:****Remark:** Toxic for fish**Additional ecological information:****General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**Other adverse effects** No further relevant information available.

EU

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.12.2011

Version number 5

Revision: 08.12.2011

Trade name: **Sealer MK-749**

(Contd. of page 5)

13 Disposal considerations**Waste treatment methods****Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 Must be specially treated adhering to official regulations.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14 Transport information**UN-Number**

ADR, IMDG, IATA

UN1866

UN proper shipping name

ADR

1866 RESIN SOLUTION (not viscous)

IMDG

RESIN SOLUTION, MARINE POLLUTANT

IATA

RESIN SOLUTION

Transport hazard class(es)

ADR



Class

3 Flammable liquids.

Label

3

IMDG



Class

3 Flammable liquids.

Label

3

IATA



Class

3 Flammable liquids.

Label

3

Packing group

ADR, IMDG, IATA

III

Environmental hazards:

Marine pollutant:

Yes

Symbol (fish and tree)

Warning: Flammable liquids.

Special precautions for user

Danger code (Kemler):

30

EMS Number:

F-E,S-E

Transport in bulk according to Annex II of MARPOL73/78
 and the IBC Code

Not applicable.

Transport/Additional information:

ADR

Tunnel restriction code

D/E

EU

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.12.2011

Version number 5

Revision: 08.12.2011

Trade name: Sealer MK-749

(Contd. of page 6)

15 Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations:****Technical instructions (air):****Class Share in %**

II > 50

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**16 Other information**

Chapters that were changed since the latest revision are marked with a "**".

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Department issuing MSDS: Laboratory**Contact:** Mr. Marek*** Data compared to the previous version altered.**

EU