

## Release Agent 621/E7

### Description:

Release Agent 621/E7 is a liquid, water-based external release agent, specifically developed for the purpose of processing polyurethane foams. It forms a thin film that provides good adhesion to the mold and allows the release of not yet fully cured parts. The surface quality meets the requirements of the automotive industry.

### Application Fields:

Release Agent 621/E7 is suitable for applications with semi-rigid- and rigid-polyurethanes.

### Application:

Clean the moulds thoroughly from residues of dirt and other release agents before applying Release Agent 621/E7. We recommend the use of our Cleaner R-51 for this purpose. To the clean moulds, Release Agent 621/E7 is applied as an even, thin film using a spray gun. We recommend to use an airmix sprayer, as experience shows that very regular films can be achieved in this way. Before the processing can be started, the release agent has to be well dried.

### Technical Data:

<b>Composition:</b>	aqueous emulsion of different waxes and polymers, silicone-free
<b>Appearance:</b>	white liquid
<b>Density [g/cm<sup>3</sup>]:</b>	approx. 0.95
<b>pH-value (20°C):</b>	approx. 10

### Packaging:

Can	28.5 kg
Drum	190 kg

### Storage:

Release Agent 621/E7 should be stored in tightly sealed containers and has to be protected from frost, heat and direct sunlight. If these rules are obeyed, the product can be stored for at least 6 months. The expiry date is stated beneath the production date on the labels of each container.

**Information for regulations on safety and transportation are provided in the safety data sheet**

**Further information:**

Product technical information and data is based on the best information available and does not constitute or imply a warranty or patent infringement of any kind. The user is responsible for testing product suitability prior to use in production.

Page: 1 of 1  
Revision: 30.06.2009 RR/ts  
Print: 28.05.2010