

Anti-Corrosive MAC-6146

Description:

Anti-Corrosive MAC-6146 is a water-based product to treat metal surfaces. The product has been developed specifically to protect metal moulds from corrosion during storage. The special composition with high quality raw materials allows to eliminate solvent in the formulation. Other than standard anti-corrosive products, Anti-Corrosive MAC-6146 allows an immediate coating (e.g. release agent) on the treated surface without extra cleaning.

Application Fields:

Anti-Corrosive MAC-6146 is suitable for applications on all metal surfaces and operating temperatures of up to 260°C. Anti-Corrosive MAC-6146 is mostly used after mould cleaning in the tire industry.

Application:

After cleaning of the metal surface Anti-Corrosive MAC-6146 is to be applied to the cold metal surface. The product can be applied in any way (ex. spraying, brushing, dipping), depending on the operators preference. During application it is important to treat all details of the surface that shall be protected against corrosion. After application the treated part has to dry and can then be stored as usual.

Technical Data:

Composition:	wetting- and anti corrosive agents dissolved in water
Appearance:	colourless liquid
Density [g/cm³]:	Approx. 1.01
pH-value (20°C):	Approx. 11

Packaging:

Can	30 kg
Drum	200 kg

Storage:

Anti-Corrosive MAC-6146 should be stored in tightly sealed containers and has to be protected from frost, heat and direct sunlight. If these rules are obeyed, the product can be stored for at least 6 months. The expiry date is stated beneath the production date on the labels of each container.

Information for regulations on safety and transportation are provided in the safety data sheet

Further information:

Product technical information and data is based on the best information available and does not constitute or imply a warranty or patent infringement of any kind. The user is responsible for testing product suitability prior to use in production.

Page: 1 of 1
Revision: 16.06.2009 FS/ts
Print: 25.05.2010



Viernheimer Str. 70-76
D-69469 Weinheim
Postfach 10 07 29
D-69447 Weinheim

Geschäftsführer: Wilhelm Münch
Amtsgericht Mannheim HRB 431102

Tel +49 (0)6201/99 83-0
Fax +49 (0)6201/99 83-66
info@muench-chemie.com
www.muench-chemie.com

USt.-IDNr. DE 144497299
Steuer-Nr. 47020/10016

Bankverbindungen Weinheim:

Deutsche Bank AG
BLZ 670 700 24
Kto. 586 896 300
Swift Code/BIC: DEUT DE DB 670
IBAN: DE84 6707 0024 0586 8963 00

Volksbank eG
BLZ 670 923 00
Kto. 1 078 801
Swift Code/BIC: GENO DE 61 WNM
IBAN: DE40 6709 2300 0001 0788 01