

Lubricant MK-8020

Description:

Lubricant MK-8020 is a ready to use product on water basis which has been developed for the assembly of profiles. Lubricant MK-8020 provides an excellent slip effect and does not leave any visible residues on surface of the treated parts.

Application Fields:

Lubricant MK-8020 is suitable for the assembly of any kind of profile.

Application:

Depending on the application Lubricant MK-8020 can be applied by brushing, wiping or spraying. If the application requires parts can also be dipped into a tank filled with Lubricant MK-8020.

Technical Data:

Composition:	combination of polymers in aqueous formulation
Appearance:	cloudy colourless liquid
Density [g/cm³]:	approx. 1
pH-value (20°C):	approx. 7

Packaging:

Can	30 kg
Drum	200 kg

Storage:

Lubricant MK-8020 should be stored in tightly sealed containers and has to be protected from frost, heat and direct sunlight. If these rules are obeyed, the product can be stored for at least 12 months. The expiry date is stated beneath the production date on the labels of each container.

Information for regulations on safety and transportation are provided in the safety data sheet

Product technical information and data is based on the best information available and does not constitute or imply a warranty or patent infringement of any kind. The user is responsible for testing product suitability prior to use in production.

Further information:

Page: 1 of 1
Revision: 09.06.2009 FS/fs
Print: 26.05.2010