

# Lubricant MK-YG/11 F

## Description:

Lubricant MK-YG/11 F is a water-based "ready-to-use" - lubricant, specifically developed as a mounting-aid for mounting tires onto rims. Lubricant MK-YG/11 F is silicone-, solvent- and soap-free and provides very good slip properties to help mounting tires, without leading to an undesired rim slip during inspection of the tire. When using MK-YG/11 F for tire uniformity measurement, reproducibility of the measured values is at the optimum (e.g. 5x5 test). By eliminating soap from the formulation, an almost neutral pH-value can be guaranteed, which also helps to prevent corrosion. The maintenance intervals for sealings in the supply pipes can be extended, since those will not be attacked by alkaline mediums anymore. Special additives in the formulation accelerate the evaporation of the product after the application to the tire.

## Application Fields:

Lubricant MK-YG/11 F is suitable as a mounting lubricant for all tire- and rim- types.

## Application:

Lubricant MK-YG/11 F can be applied by brushing, wiping or spraying as preferred by the customer.

## Technical Data:

<b>Composition:</b>	combination of polymers in aqueous formulation
<b>Appearance:</b>	colourless liquid
<b>Density [g/cm<sup>3</sup>]:</b>	approx. 0.99
<b>pH-value (20°C):</b>	approx. 8

## Packaging:

Can	30 kg
Drum	200 kg

## Storage:

Lubricant MK-YG/11 F should be stored in tightly sealed containers and has to be protected from frost, heat and direct sunlight. If these rules are obeyed, the product can be stored for at least 6 months. The expiry date is stated beneath the production date on the labels of each container.

**Information for regulations on safety and transportation are provided in the safety data sheet**

**Further information:**

Product technical information and data is based on the best information available and does not constitute or imply a warranty or patent infringement of any kind. The user is responsible for testing product suitability prior to use in production.

Page: 1 of 1  
Revision: 30.06.2009 RR/ts  
Print: 26.05.2010



Viernheimer Str. 70-76  
D-69469 Weinheim  
Postfach 10 07 29  
D-69447 Weinheim

Tel +49 (0)6201/99 83-0  
Fax +49 (0)6201/99 83-66  
info@muench-chemie.com  
www.muench-chemie.com

Bankverbindungen Weinheim:

Deutsche Bank AG  
BLZ 670 700 24  
Kto. 586 896 300  
Swift Code/BIC: DEUT DE DB 670  
IBAN: DE84 6707 0024 0586 8963 00

Volksbank eG  
BLZ 670 923 00  
Kto. 1 078 801  
Swift Code/BIC: GENO DE 61 WNM  
IBAN: DE40 6709 2300 0001 0788 01

Geschäftsführer: Wilhelm Münch  
Amtsgericht Mannheim HRB 431102

USt.-IDNr. DE 144497299  
Steuer-Nr. 47020/10016