

Release Agent MPU-4022

Description:

Release Agent MPU-4022 is a liquid, external release agent, based on solvents. Release Agent MPU-4022 has been specifically designed for the purpose of processing polyurethane foams. It forms a very thin film to provide good release between the mold surface and the material to be processed.

Application Fields:

Release Agent MPU-4022 is suited for processing cast urethane and rigid foam. The product can be used with polyether- as well as with polyester- systems.

Application:

Prior to the first application of Release Agent MPU-4022, thoroughly clean the moulds from dirt and release agent residues. We highly recommend the use our product Cleaner R-51. Apply a thin and even layer of Release Agent MPU-4022. Commence by starting up the production.

Technical Data:

Composition:	mixture of resins in solvent
Appearance:	white liquid
Density [g/cm³]:	approx. 0.79
Flashpoint [°C]:	25

Packaging:

Can	22.5 kg
Drum	150 kg

Storage:

Release Agent MPU-4022 should be stored in tightly sealed containers and has to be protected from frost, heat and direct sunlight. If these rules are obeyed, the product can be stored for at least 12 months. The expiry date is stated beneath the production date on the labels of each container.

Information for regulations on safety and transportation are provided in the safety data sheet

Product technical information and data is based on the best information available and does not constitute or imply a warranty or patent infringement of any kind. The user is responsible for testing product suitability prior to use in production.

Further information:

Page: 1 of 1
Revision: 31.05.2010 RR/cw
Print: 31.05.2010