

Release Agent MP-5104

Description:

Release Agent MP-5104 is a water-based "ready-to-use" release agent, forming a coherent release film on the mould. Though this film is micro thin, it is very resistant after cure, even to abrasive materials. Release Agent MP-5104 is temperature stable up to 200°C. Release Agent MP-5104 develops a strong chemical bonding to most mould materials and thus provides multiple releases per application. Release Agent MP-5104 does not transfer to the moulded parts, allowing further processing like varnishing or gluing without subsequent treatment. Build-ups on the mould, caused by depositions of pigments, anti-aging agents, resin residues etc. are reduced considerably. A build-up caused by Release Agent MP-5104 is unlikely if it is used as directed.

Application Fields:

Release Agent MP-5104 is suited as a release agent for the processing of cotton fibre sheets.

Application:

The first step is to thoroughly clean the mould. We recommend to clean the molds with a fast evaporating solvent to be sure to have eliminated all grease- or wax- residues. As a priming coat, 1-2 thin uniform layers of the release agent are applied to the hot mould. Longer drying time and higher temperature will result in an improved durability and an increased number of possible releases per application. After this pretreatment the processing can be started. To refresh the release film, it is sufficient to reapply a single and thin coat of Release Agent MP-5104, under considerations of the drying time.

Technical Data:

Composition:	aqueous emulsion of synthetic resins, solvent-free
Appearance:	whitish Fluid
Density [g/cm³]:	approx. 1
pH-value (20°C):	approx. 7

Packaging:

Can	30 kg
Drum	200 kg

Storage:

Release Agent MP-5104 should be stored in tightly sealed containers and has to be protected from frost, heat and direct sunlight. If these rules are obeyed, the product can be stored for at least 6 months. The expiry date is stated beneath the production date on the labels of each container.

Information for regulations on safety and transportation are provided in the safety data sheet

Product technical information and data is based on the best information available and does not constitute or imply a warranty or patent infringement of any kind. The user is responsible for testing product suitability prior to use in production.

Further information:

Page: 1 of 1
 Revision: 30.06.2009 RR/ts
 Print: 30.06.2009



Viernheimer Str. 70-76
 D-69469 Weinheim
 Postfach 10 07 29
 D-69447 Weinheim

Geschäftsführer: Wilhelm Münch
 Amtsgericht Mannheim HRB 431102

Tel +49 (0)6201/99 83-0
 Fax +49 (0)6201/99 83-66
 info@muench-chemie.com
 www.muench-chemie.com

USt.-IDNr. DE 144497299
 Steuer-Nr. 47020/10016

Bankverbindungen Weinheim:

Deutsche Bank AG
 BLZ 670 700 24
 Kto. 586 896 300
 Swift Code/BIC: DEUT DE DB 670
 IBAN: DE84 6707 0024 0586 8963 00

Volksbank eG
 BLZ 670 923 00
 Kto. 1 078 801
 Swift Code/BIC: GENO DE 61 WNM
 IBAN: DE40 6709 2300 0001 0788 01